

HOW TO OPEN THE RENUSURFACE CARBOY.



THE FOLLOWING INSTRUCTIONS WILL ASSIST YOU IN
OPENING THE **RENUSURFACE** 5-GALLON CARBOY CONTAINER.

1

GATHER THE NECESSARY TOOLS

You will need a 3/4" drill bit or socket extender and necessary safety equipment.

2

PLACE THE CARBOY ON A FLAT SURFACE

Place the Carboy on a flat surface and at an appropriate height for you to safely use the cordless drill or socket extender. Ensure the Carboy is in a location that is a safe distance from anything that could be damaged if it were to accidentally tip over while opening the container.

3

OPEN THE CARBOY

Using one of the following two options, open the carboy.

- **Option 1:** Using a cordless drill with a 3/4" Spade/Paddle drill bit or a hole saw bit, drill out the Carboy opening. It is okay if the inner piece of plastic falls into the Carboy. Screw the faucet spout clockwise into the Carboy opening.
- **Option 2:** Using a blunt 3/4" socket extender, hammer the socket extender into the Carboy opening until the inner section gives way. Be careful not to drop the socket extender you are using into the Carboy. Again, it is okay if the inner plastic piece falls into the Carboy. Screw the faucet spout clockwise into the Carboy opening.

4

DISPENSE THE PRODUCT

Turn the vent cap counterclockwise prior to dispensing the product.

EXPERIENCE SOMETHING NU.

For detailed usage instructions, scan the code with your mobile device or visit:

NuVinAir.com/treatments

